



3-PLY PROCEDURE MASKS – ASTM Level 3

Technical Data Sheet



Intended Use:

These US made 3-ply procedure masks are intended for single use by healthcare professionals to protect both patients and healthcare workers against transfer of microorganisms, bodily fluid, and airborne particulates.

These procedure masks are intended for use in infection control practices to reduce the potential exposure to blood and bodily fluid.

Material:

- Nonwoven spunbond for outer and inner layers
- Nonwoven meltblown for filtration layer
- Poly-spandex ear loops
- Not made with natural rubber latex
- Non-sterile

Size:

- One size fits most

Color:

- Blue

PACKAGING

| Item# | Description | Quantity |
|--------|--|-----------------|
| PM3003 | Level 3, 3-Ply Procedure Mask, Universal | 50/Bx, 24 Bx/Cs |



3-PLY PROCEDURE MASKS – ASTM Level 3

Technical Data Sheet (Continued)

Performance:

ASTM LEVEL 3 BARRIER Per Current ASTM F2100 Requirements

| | |
|--|-----------|
| BFE % | ≥ 98% |
| PFE% | ≥ 98% |
| ΔP (mmH ₂ O/cm ²) | < 6.0 |
| Fluid Resistance | 160 mm Hg |
| Flame Spread | Class 1 |



Warning/Caution Statements:

- Masks help to protect the wearer against the transfer of microorganisms, bodily fluids, and particulate materials but do not eliminate exposure to the risk of disease or infection.
- These masks should be disposed of after each use.
- Masks should be stored in a cool and dry place.
- Discontinue use if masks have any signs of damage.

Authorization:

- FDA 510(K)